## **Draw Wire Encoder**

Mini Size: 30x30mm; Measurement Range:0-500mm; Output Analog:0-10v, 4-20mA

## **GI-D15 Series**

💽 CE 🎑



Size:30 x 30mm Hub:40/50mm

- Measurement Range: 0-500mm;
- ► Supply Voltage:24v;
- Output Format: Analog-0-10v, 4-20mA;

▶ Widely used in various fields of automatic control and measurement system, such as machinery manufacturing, shipping, textile, printing, aviation, military industry Testing machine, elevator, etc.

► Vibration-resistant, corrosion-resistant, pollution-resistant;

Product characteristics	
Size:	30mm x 30mm, Hub: 40/50mm;
Measurement Range:	0-500mm;
Electrical Data	
Output Format:	Analog 0-10v, 4-20mA
Insulation resistance	Min 1000 Ω
Power	2W
Supply Voltage:	24v
Mechanical Data	
Accuracy	0.2%
Linear Tolerance	±0.1%
Wire Rope Dia.	0.6mm
Pull	2.5N
Pulling Speed	Max.80mm/s
Working Life	Min.50000h
Case Material	Metal
Cable Length	1m 2m or as per requested
Environment Data	
Working Temp.	-25~80℃
Storage Temp.	-30~80℃
Protection Grade	IP54

## Dimensions



